



13046 RACETRACK RD SUITE 187 TAMPA FL 33626

EAG-LED PANEL LIGHT

EAG-PLS-40W



Advantages

- CE RoHS TUV UL DLC certificate
 - High CRI
 - External driver, input voltage AC100-277V
 - No UV or IR in the beam
 - Easy to install and operate
 - Fully Dimmable
 - Motion Sensor Capabilities
 - Instant start, NO flickering, NO humming
 - Green and eco-friendly without mercury
-

WWW.EAG-LED.COM



13046 RACETRACK RD SUITE 187 TAMPA FL 33626

EAG-PLS-40W Technical Data

Color temperature	3000-5500K
CRI	>80
Lumen	4800LM
Lumen Efficacy	120 lm/w
Input Power	40W
Viewing Angle	120 Degree
Input Voltage	AC100-277V
Frequency Range	50-60 HZ
PFC	>90%
Life Span	50000 Hours
Waterproof Rating	IP41
Operating Temperature	-20°C TO 45 °C
Operating Humidity	20%-70% RH
Storage Temperature	-30°C TO 80 °C
Storage Humidity	10%-75% RH
Application	Indoor
Certification	UL DLC CE RoHS TUV
Housing	Aluminum
Light guide plate	PMMA





13046 RACETRACK RD SUITE 187 TAMPA FL 33626

Applications

Widely used in supermarkets, offices, hotels, hospitals, schools, meeting rooms, in a library, or residential, etc.



BEFORE

AFTER