



13046 Race Track Rd. #187
Tampa, FL 33626
(813) 463-2420
www.eag-led.com

WALL PACK LIGHT



Advantages

- UL cUL DLC certificate
- IP65 Internal driver
- Input voltage 100-277VAC
- No UV or IR in the beam
- Energy efficient, long lifespan
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.

Applications

- Industrial lighting, Entrance Lighting
- Landscaping lighting, Courtyard, Hotels



13046 Race Track Rd. #187
 Tampa, FL 33626
 (813) 463-2420
 www.eag-led.com

WALL PACK LIGHT

Technical Specifications

Color Temperature	3000 – 5700K	Waterproof Rating	IP65
CRI	>80	Operating Temperature	-20°C TO 45°C
Lumen	13800– 15000LM	Operating Humidity	20% - 90% RH
Input Power	120W	Storage Temperature	-30°C TO 80°C
Viewing Angle	110 Degree	Storage Humidity	10% - 95% RH
Input Voltage	50-60 HZ	Application	Outdoor/Indoor
PFC	>.9	Certification	UL cUL DLC
Housing color	Brown	Housing	Aluminum

Product Specifications		Materials	
Product Name	LED Wall Pack Light	LED Qty	420 PCS
Part Number	EAG-WP-120W	LED Type	2835, .5W
Dimension	459*248*223mm		



13046 Race Track Rd. #187
 Tampa, FL 33626
 (813) 463-2420
 www.eag-led.com

WALL PACK LIGHT

Testing Parameters

DATA OF LAMP		PHOTOMETRIC DATA Eff: 122.50 lm/W			
MODEL		I _{max} (cd)	5323	S/MH (C0/180)	1.20
NOMINAL POWER (W)	120	LOR (%)	100.0	S/MH (C90/270)	0.64
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	14777	η UP, DN (C0-180)	19.4, 66.9
NOMINAL FLUX (lm)	14776.7	CIE CLASS	SEMI-D.	η UP, DN (C180-360)	0.6, 13.1
LAMPS INSIDE	1	η up (%)	20.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120.0	η down (%)	80.0	CIBSE SHR MAX	1.30

