

13046 Race Track Rd. #187 Tampa, FL 33626 (813) 463-2420 www.eag-led.com

PANEL LIGHT



Advantages

- TUV DLC CE RoHS certificate
- High CRI
- External driver, Input voltageAC85-265v
- No UV or IR in the beam
- Easy to install and operate
- Energy efficient, long service life
- Light is soft and uniform
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.

Applications

- Supermarkets, Hotels, Libraries
- Offices, Schools, Meeting rooms



13046 Race Track Rd. #187 Tampa, FL 33626 (813) 463-2420 www.eag-led.com

PANEL LIGHT



Technical Specifications

Color Temperature	2700-8000K	Waterproof Rating	IP41
CRI	>80	Operating Temperature	-20°C TO 45°C
Lumen Efficacy	130 lm/w	Operating Humidity	20% - 70% RH
Input Power	50W	Storage Temperature	-30°C TO 80°C
Viewing Angle	120 Degree	Storage Humidity	10% - 75% RH
Input Voltage	AC85-265V	Application	Indoor
Frequency	50-60 HZ	Certification	CE DLC RoHS TUV
PFC	>.9	Housing	Aluminum

Product Specifications

Product Name LED Panel Light		Emergency Backup option Built in Lithium Battery; test button and indicator light;	
Part Number	EAG-PLR-50W	emergency working time 90 mins	
Dimensions	600mm*1200mm	Operating hours 50,000 hrs	