





PANEL LIGHT

EAG-LED super high quality Panel Lights offer a high CRI, external driver, with soft and uniform light in seven wattage and size options.

They are lightweight and easy to operate, energy efficient and provide a long service life.

PMMA Acrylic, no yellow, also available with a dimmable option





PANEL LIGHT

Advantages

- No Flickering
- Instant start, no hum
- IP41 driver
- Input voltage 85-265 Vac
- No UV or IR in the beam
- Energy Efficient, Long Lifespan
- Light is soft and uniform
- Green and eco-friendly
- No mercury

Applications

- Super Markets
- Hotels
- Libraries
- Schools
- Meeting Rooms
- Offices



PANEL LIGHT

	EAG-PLS-30	EAG-PLR-30	EAG-PLS-40	EAG-PLR-40
INPUT POWER	30W	30W	40W	40W
LED DRIVER	IP 41	IP 41	IP 41	IP 41
LUMINOUS EFFICIENCY	110-130 LM/W	110-130 LM/W	110-130 LM/W	110-130 LM/W
COLOR TEMPERATURE	3000-5500K	3000-5500K	3000-5500K	3000-5500K
CRI	>80	>80	>80	>80
BEAM ANGLE	120 Degree	120 Degree	120 Degree	120 Degree
FIXTURE SIZE FEET	2 X 2	1 X 4	2 X 2	1 X 4
WORKING TEMPERATURE	-20°C TO 45°C	-20°C TO 45°C	-20°C TO 45°C	-20°C TO 45°C
STORAGE TEMPERATURE	-30°C TO 80°C	-30°C TO 80°C	-30°C TO 80°C	-30°C TO 80°C
RATING	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
HOUSING	Aluminum	Aluminum	Aluminum	Aluminum



PANEL LIGHT

	EAG-PLR-48	EAG-PLR-50	EAG-PLS-50	EAG-PLR-60
INPUT POWER	48W	50W	50W	60W
LED DRIVER	IP 41	IP 41	IP 41	IP 41
LUMINOUS EFFICIENCY	110-130 LM/W	110-130 LM/W	110-130 LM/W	110-130 LM/W
COLOR TEMPERATURE	3000-5500K	2700-8000K	2700-8000K	2700-8000K
CRI	>80	>80	>80	>80
BEAM ANGLE	120 Degree	120 Degree	120 Degree	120 Degree
FIXTURE SIZE FEET	2 X 4	2 X 4	2 X 2	2 X 4
WORKING TEMPERATURE	-20°C TO 45°C	-20°C TO 45°C	-20°C TO 45°C	-20°C TO 45°C
STORAGE TEMPERATURE	-30°C TO 80°C	-30°C TO 80°C	-30°C TO 80°C	-30°C TO 80°C
RATING	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
HOUSING	Aluminum	Aluminum	Aluminum	Aluminum



BETTER
LIGHTS
FOR A BETTER
WORLD

EAG-LED GLOBAL

13046 Racetrack Rd • Tampa, FL 33626
813.463.2420 • savings@eag-led.com



www.eag-led.com