

tundo



TUNABLE PANEL LIGHT

EAG-LED super high quality Tunable Panel Lights offer a high CRI, external driver, with soft and uniform light in adjustable wattage and three size options.

They are lightweight and easy to operate, energy efficient and provide a long service life.

PMMA Acrylic diffuser to eliminate yellowing, available with a dimmable option







TUNABLE PANEL LIGHT

Advantages

- Flicker Free Driver
- Instant start, no hum
- CCT and Watt Tunable
- 0-10V Dimable
- Input voltage 120-277 VAC
- No UV or IR in the beam
- UL Rated, DLC Premium
- Green and eco-friendly
- No mercury, 50,000 Life Span
- Acrylic diffuser to eliminate yellowing

Applications

- Super Markets
- Hotels, Restaurants
- Libraries
- Schools, Classrooms
- Meeting Rooms
- Offices
- Medical Facilities
- Bus Station, Stores



TUNABLE PANEL LIGHT

	EAG-PLS-T	EAG-PLR1X4-T	EAG-PLR-T
INPUT POWER	20W, 25W, 30W, 35W	20W, 25W, 30W, 35W	35W, 40W, 45W, 50W
LUMINOUS EFFICIENCY	125 LM/W	125 LM/W	125 LM/W
COLOR TEMPERATURE	3000, 4000, 4500, 5000K	3000, 4000, 4500, 5000K	3000, 4000, 4500, 5000K
CRI	>80	>80	>80
BEAM ANGLE	120 Degree	120 Degree	120 Degree
FIXTURE SIZE FEET	2 X 2	1 X 4	2 X 4
Working temperature	-20°C TO 45°C	-20°C TO 45°C	-20°C TO 45°C
STORAGE TEMPERATURE	-25°C TO 65°C	-25°C TO 65°C	-25°C TO 65°C
RATING	50,000 hrs	50,000 hrs	50,000 hrs
HOUSING	Aluminum	Aluminum	Aluminum



EAG-LED GLOBAL

13046 Racetrack Rd • Tampa, FL 33626 813.463.2420 • savings@eag-led.com











www.eag-led.com